



Photo by Sgt. Zachary Catron

Features and Benefits

- Evolution Series iDX 3.4 and above, Velocity Capable (ARSTRAT Certified)
- Embedded carrier monitor enabling pointing and acquisition of the satellite signal over a web user interface
- Global broadcast system (GBS) in MPE mode
- Web-based user interface (WUI) for real-time monitoring, configuring and commissioning the satellite router
- Signal strength and network status LEDs to enhance ease of use
- Ruggedized for the harshest environments with -40°C to +50°C and waterproof enclosure (method 506.5, procedure 1)

GATR 950 iDirect Modem

Ideal for mobile/transportable communications and packed with features, including built-in pointing assistance with numerical signal display on the modem and a web-based user interface, The GATR 950 iDirect is a compact, rugged outdoor modem based on iDirect Velocity™ and Evolution technology.

Engineered to operate in the harshest environments with an operating range of -40°C to +50°C, the waterproof enclosure and easy to understand status LED's on the GATR 950 modem ensure stable communications no matter where your mission takes you.

Specifications

Configuration	
Network Topology	Star
Modulation	DownStream
	UpStream
Max Rates	Symbol
	Spreading Factor
Spread Spectrum	Max Chip Rate
	LAN
Data and M&C	Console
	Auxiliary Interfaces
Interfaces	
SatCom	Tx Out
	Rx In
	Rx Out
Data and M&C	LAN
	Console
Auxiliary Interfaces	
Features and Compatibility	
Protocols Supported	TCP, UDP, ICMP, IGMP, RIP v2, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, cRTP, and GRE
Security	AES Link Encryption (256-bit), TRANSEC, FIPS 140-2 Level 3 Compliant, x.509 digital certificates authentication, Automatic Key Management
Traffic Engineering	Group QoS, QoS (Priority Queing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting
Other Features	Built-in Automatic Uplink Power, Frequency and Timing Control (star), Authentication, Antenna Control Interface (OpenAMIP), Multi-Protocol Encapsulation, Low-speed COTM
Carrier Monitor	Web User Interface, RF Tuning Range
	RF Channel Bandwidth
	RX Gain Range
Mechanical and Environmental	
Size	16.5" H x 7.75" W x 2.5" D (320 in3)
Weight	8.2 lbs
Operating Temperature	-40°C to +50°C
Other	Tested to MIL-STD-810G shock, vibration, altitude, blowing rain, blowing sand & dust, ice load, humidity, solar and MIL-STD-461F Electromagnetic Interference
Input Voltage	18 - 36 VDC



Front



Rear

CHANGING THE SHAPE OF SATCOM

Cubic is revolutionizing the ultra-portable SATCOM industry with its inflatable communications terminal. Compared to other deployable rigid dishes of comparable size, GATR's unique shape and designs enable extreme portability, lower cost of ownership, reliability in extreme environments and ease of set up.

THE APPEARANCE OF U.S. DEPARTMENT OF DEFENSE (DOD) VISUAL INFORMATION DOES NOT IMPLY OR CONSTITUTE DOD ENDORSEMENT.