



FE3 CAMERA

FE3, the latest Gridsmart iconic bell camera, is enhanced to support High Dynamic Range (HDR) video. With HDR, the FE3 offers significantly improved capabilities tracking vehicles entering and exiting the intersection by creating clear, high-quality images even in challenging lighting conditions. Our FE3 HDR technology improves visibility by utilizing a wider range of brightness, delivering greater detection accuracy even in low-light situations. The rugged aluminum hardware is built to withstand the elements, and the single-wire system is a quick install in three (3) hours or less, saving you time and money in installation and upkeep.



SPECIFICATIONS

CONNECTIVITY

Single CAT5e Cable

DIMENSIONS

8.0" diameter x 13.5" (20.3 cm diameter x 34.3 cm)

WEIGHT

6.1 lbs (2.8 kg)

ENVIRONMENT

-29°F to 165°F (-34°C to 74°C)

0%-100% Humidity

5-30Hz Vibration

10G Shock

POWER

Power over Ethernet (PoE)

CONSUMPTION

50W Max

REGULATORY

FCC Class A

IMAGE FORMAT

MJPEG Color

FEATURES

APPLICATIONS

Single camera detection and counting

Highway counting and monitoring

CAMERA

CMOS Sensor

Power over Ethernet (PoE)

Thermostatically Controlled Heaters

Waterproof and Dust-Tight