

Features and Benefits

- Compact Size and Weight


 Greater than 10X reduction over traditional technologies
- Near Ideal Performance
 Higher rejection and flatter passbands
- Precision

 Low part-to-part variation
- Ease of Assembly
 -Standard SMT processes
- Lower System BOM Cost

 Eliminate extra gain stages and signal cleanup

Applications

- Metrology
- RF Telemetry
- Meterology
- Instrumentation
- 5G Backhaul
- Satellite Communications



V Band Bandpass Filter

Surface mount millimeter-wave bandpass filter with unrivaled rejection, and flatness — in a miniature form factor.

Description

Nuvotronics PolyStrata® Technology delivers performance and precision for your front-end systems. This bandpass filter is a surface-mount interdigital filter with unparalleled flatness and high frequency performance.

This PSF42B04S part has a passband of 40 GHz – 44 GHz with a characteristic impedance of 50 Ω . The low loss performance of this part is ideal for space or ground applications. This part is compliant with RoHS standards. Tape and reel packaging is available for bulk orders.

Typical Electrical Performance

Return Loss, 40 GHz to 44 GHz Rejection at 38.5 GHz Rejection at 45.7 GHz Rejection at 36 GHz Rejection at 48 GHz Rejection at 48 GHz Rejection at 48 GHz	Parameter	Value	Y	
Rejection at 38.5 GHz Rejection at 45.7 GHz Rejection at 36 GHz 16 dB 31 dB Rejection at 48 GHz 31 dB	Insertion Loss, 40 GHz to 44 GHz	2.2 dB		10.22
Rejection at 45.7 GHz Rejection at 36 GHz Rejection at 48 GHz 31 dB	Return Loss, 40 GHz to 44 GHz	12 dB	-20	\mathcal{W}
Rejection at 45.7 GHz 16 dB 40 Rejection at 36 GHz 31 dB	Rejection at 38.5 GHz	16 dB		ų v
Rejection at 48 GHz	Rejection at 45.7 GHz	16 dB		1
	Rejection at 36 GHz	31 dB	-50	1
	Rejection at 48 GHz	31 dB	-60	
			0 10 20 30 40 F [GHz]	J

Cubic Mission Solutions SPECIFICATION SHEET | P/N 1013497




Absolute Maximum Ratings

Power	2W CW
Operating Temp	-55°C to 125°C
Solder Reflow	260°C max. for 10 seconds, 3 cycles
Epoxy Attach	150°C max. for 90 minutes


Additional Details

Special Handling / Storage Instructions		
Storage	IAW IPC-4553A	
EDS Sensitivity	None	
Moisture Sensitivity	MSL3	
Ordering Information	1013497	
Standard Packaging	Tape and Reel Conforms to EIA-481-E	
Alternative Packaging Available	Gel-coated Substrate Carrier Waffle pack	
Component Termination Finish	Immersion Silver	
Certifications	RoHS Compliant	


Simplified Block Diagram




PCB Layout



Tape and Reel



Component View



Mechanical Drawing

